THE IDEAL SOLUTION FOR

RAPID DEPLOYMENT OF **MACHINE TO MACHINE COMMUNICATIONS**





THE STAND A LONE M ODEM

InterCEL Pty Ltd has proven its expertise in the field of cellular communications in almost wo decades of doing business. Industry experts recognize InterCEL's knowledge and expertise in the realm of machine to machine communications, by our commitment to quality products, superior service and technical support that deliver outstanding results every time all the time. The SAM modem with RJ45 connection, is the third in a series of successful technical innovations in GSM/GPRS modems, designed, manufactured and sold by InterCEL. Proven worldwide in both Europe and Asia, the SAM modem is deployed with confidence throughout Australia for Machine to Machine Communications, as used by leading Australian and International electricity meter manufacturers and Electricity Distributors for robust and reliable AMR communications."



Product BENEFIT

- 4 Proven Worldwide
- 4 Faster Time to Market
- **4** Simple Integration
- 4 Fully Type Approved
- 4 Australian Networks Approved
- 4 A-Ticked
- 4 Plug and Play Installation
- 4 Also Available in CDMA



- 4 Dual-band External Modem GSM/GPRS 900/1800 MHz
- 4 Fully Type Approved for Phase

Specifications 4 SMS, fax, CSD,

GPRS Class 10 4 Easy Control

by AT Commands 4 Auto Reset

















INTER CEL

go anywhere communication & data transfer







NETWORK INDEPENDENCE



SAM DE MODEM

Product Features

- 4 GSM/GPRS Dual Band 900/1800MHz
- 4 ETSI GSM Phase 2+ standard
- 4 Class 4 (2W at 900MHz), Class1 (1W at 1800MHz)
- 4 Fax, SMS and Data (CSD and GPRS) Capability
- 4 Input voltage connector: 2-wire or through the 4-pin MICROFIT (optional)
- 4 RS232 data connector: 8-contact RJ45 socket (RJ45-to-DB9 cable available)
- 4 Antenna connector : standard FME male

Electrical

- 4 Input voltage range: 5.5V to 32V
- 4 Max 9mA @ 12V in idle mode
- 4 Max 400mA @ 12V in communications mode for 900MHz band
- 4 Max 160mA @ 12V in communication mode for 1800MHz band
- 4 Peak 1.8A @ 5.5V
- 4 3V SIM (only)
- 4 Operating temperature -20°C to + 55°C
- 4 Storage temperature -25°C to + 70°C

GSM Data/Fax features

- 4 CSD: asynchonous, transparent and non transparent, up to 14400bps
- 4 Automatic Fax Group 3 (Class 1 and Class 2)
- 4 MNP2, V.42bis

GPRS Packet data features

- 4 GPRS Class 10
- 4 PBCCH support
- 4 Coding schemes CS1 to CS4
- 4 Compliant with SMG31bis
- 4 Optional embedded TCP/IP stack

SMS features

- 4 Text and PDU
- 4 Point to point (MO/MT)
- 4 Cell broadcast

Other Features

- 4 ME + SIM phone book management
- 4 Fixed dialing number
- 4 SIM tool kit class 2
- 4 SIM, network and service provider lock
- 4 Real time clock
- 4 Alarm management
- Software upgradable
- 4 UCS2 character set management
- 4 RS232 Terminal speed from 300bps to 115200bps
- 4 Sliding SIM holder (3V SIM only)

InterCEL Pty Ltd may at any time and with out notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them.



THE IDEAL SOLUTION FOR

RAPID DEPLOYMENT OF **MACHINE TO MACHINE COMMUNICATIONS**













"InterCEL Pty Ltd has proven its expertise in the field of cellular communications in almost two decades of doing business. Industry experts recognize InterCEL's knowledge and expertise in the realm of machine to machine communications, by our commitment to quality products, superior service and technical support that deliver outstanding results every time all the time. The SAM modem with RJ45 connection, is the third in a series of successful technical innovations in GSM/GPRS modems, designed, manufactured and sold by InterCEL. Proven worldwide in both Europe and Asia, the SAM modem is deployed with confidence throughout Australia for Machine to Machine Communications, as used by leading Australian and International electricity meter manufacturers and Electricity Distributors for robust and reliable AMR communications."









PRODUCT BENEFIT SAM FROM INTERCEL

- 4 Proven Worldwide
- **4 Faster Time to Market**
- 4 Simple Integration
- 4 Fully Type Approved
- 4 A-Ticked
- 4 Plug and Play Installation
- 4 Also Available in CDMA
- 4 Dual-band External Modem GSM/GPRS 900/1800 MHz
- 4 Fully Type Approved for **GSM Phase 2+ Specifications**
- 4 Australian Networks Approved 4 SMS, Fax, CSD, GPRS Class 10
 - 4 Easy Control by AT Commands
 - 4 Auto Reset

InterCEL Pty Ltd: 33 Glenvale Cresent, Mulgrave, 3170 Australia. Ph: +61 3 9561 1666 Fax: +61 3 9561 2614 email: intercel@intercel.com.au www.intercel.com.au ToIl free number for NZ customers 0800 742 600

Phân phối tại Việt Nam

CÔNG TY CP iNET | Số 09 Tô Hiến Thành, Q.10, HCM | Hotline: 0904885059

IEL: +84.904885059; +84.994627086 | FAX: +84.839797242 | http://inet.divivu.com



